

VALVE AND/OR FDC APART FROM RPDA

NOTES:

- VALVE BOX AND LID SHALL BE PER CHWD DETAIL VB_810.
- BOLT TORQUE ON ALL FITTINGS SHALL CONFORM TO MANUFACTURER'S SPECIFICATIONS.
- CONTACT CITRUS HEIGHTS WATER DISTRICT FOR REBAR INSPECTION PRIOR TO POURING CONCRETE. (916) 725-6873
- MATERIAL BELOW AGGREGATE BASE SHALL BE COMPACTED TO 90% MINIMUM.
- REINFORCED CONCRETE PAD SHALL BE FINISHED WITH AN EDGING TOOL AROUND THE ENTIRE PERIMETER AND BROOMED AT RIGHT ANGLES TO THE DIRECTION OF TRAVEL.
- INSTALL TAMPER SWITCHES ON BOTH OS&Y VALVES WITH CONDUIT THROUGH CONCRETE PAD PER SACRAMENTO METRO FIRE DISTRICT STANDARD.
- PAINT FIRE SPRINKLER CONNECTION USING A MANUFACTURER'S RECOMMENDED PRIMER, FINISH WITH RUSTOLEUM GLOSS WHITE, TWO COATS MINIMUM. PRIOR TO PAINTING, CLEAN ALL SURFACES WITH SOAP AND WATER USING AN ABRASIVE PAD.
- RPDA SHALL BE TESTED BY A CHWD CERTIFIED BACKFLOW PREVENTION ASSEMBLY TESTER PRIOR TO DISTRICT ACCEPTANCE OF FACILITIES.
- RPDA SHALL BE APPROVED BY THE FOUNDATION FOR CROSS CONNECTION CONTROL AND HYDRAULIC RESEARCH AT THE UNIVERSITY OF SOUTHERN CALIFORNIA.

1	FLANGE x MECHANICAL JOINT RESILIENT WEDGE GATE VALVE, VALVE RISER, AND VALVE BOX WITH LID	17	4' x 18' GALVANIZED NIPPLE
		18	4' GALVANIZED CAP
2	TAMPER SWITCH AND CONDUIT - OWNED AND MAINTAINED BY CUSTOMER	19	REINFORCED CONCRETE PAD - 4' THICK x 36' WIDE, TYPE II SIX-SACK PORTLAND CEMENT
3	90° ELBOW - DUCTILE IRON, MECHANICAL JOINT x MECHANICAL JOINT	20	3/4" CLASS II AGGREGATE BASE - 2" MINIMUM, MECHANICALLY COMPACTED TO 90%
4	DUCTILE IRON PIPE - FLANGE x PLAIN END, CL53		
5	90° ELBOW - DUCTILE IRON, FLANGE x FLANGE	21	CONCRETE DOBBIE w/ WIRE
6	REDUCED PRESSURE DETECTOR ASSEMBLY (RPDA) WITH BRASS PLUGS INSTALLED IN ALL TEST COCKS - SHALL INCLUDE 3/4" BYPASS LESS METER (5/8" x 3/4" NEPTUNE WATER METER BY DISTRICT). WILKINS 375ADA w/OS&Y VALVES OR EQUAL.		
7	TEE OR 90° ELBOW - DUCTILE IRON, MECHANICAL JOINT x MECHANICAL JOINT		
8	COMPANION FLANGE - FLANGE x 4" FIP	22	3/8" (#3) REBAR - 2" INSIDE PERIMETER
9	4" GALVANIZED NIPPLE (ADJUST LENGTH TO ACHIEVE 36" HEIGHT)	23	ASPHALT SATURATED ORGANIC FELT - (ROOFING PAPER) ASTM 30, 2 LAYERS AROUND PIPE
10	4" QUICK CHECK VALVE - FM-UL APPROVED	24	SUPPORT STAND - PLACER WATER WORKS OR EQUAL, STANDARD SADDLE HEIGHT DETERMINED IN FIELD
11	4" x 4" GALVANIZED NIPPLE	25	WEATHER FREEZE BAG w/ LOCK - POLAR BAG w/ CALLIOPE FABRIC (8-YEAR WARRANTY). CONTACT ROSEVILLE AUTO UPHOLSTERY.
12	4" GALVANIZED 90° ELBOW	26	CONCRETE BRICK - 2 1/4" x 3 3/4" x 7 1/2"
13	4" GALVANIZED TEE	27	CONCRETE THRUST BLOCK - SEE DETAIL TB_001
14	4" x CLOSE GALVANIZED NIPPLE	28	CONCRETE THRUST BLOCK - SEE DETAIL TB_001
15	4" GALVANIZED 45° ELBOW	29	#10 INSULATED COPPER LOCATOR WIRE w/ HOSE CLAMP 6' ABOVE CONCRETE PAD
16	4" x 2 @ 2 1/2" FIRE DEPARTMENT CONNECTION (FDC) w/ METALLIC BREAKABLE CAPS. PAINT WHITE.	30	3/8" NON-CASE HARDENED CHAIN AND BREAKABLE SHACKLE LOCK



**CITRUS
HEIGHTS
WATER
DISTRICT**

4", 6", 8" FIRE SPRINKLER CONNECTION

CITRUS HEIGHTS WATER DISTRICT

APPROVED BY:

Melina Rieri

DATE: 07/22/2020

CITRUS HEIGHTS WATER DISTRICT

DETAIL FOR CONSTRUCTION IN:
SACRAMENTO METRO FIRE DISTRICT

DRAWN: 21 JUL 2020

REVISED:

SCALE: N.T.S.

DESIGN: T.A.D.

CAD FILE: FP_651_1.DWG

PAGE:

FP_651_1