


**NOTES:**

1. NO PAVEMENT CUTS OR TRENCHES ARE ALLOWED IN PAVEMENT LESS THAN THREE YEARS OLD, UNLESS APPROVED BY THE CITY OF CITRUS HEIGHTS.
2. 1 1/2" DEEP GRINDING AND PAVING. GRIND TO LIP OF GUTTER, LANE LINE, OR CENTER OF TRAFFIC LANE, BUT 12" MINIMUM WIDTH.
3. SEAL COAT TREATMENT SHALL BE APPLIED AT LOCATIONS SPECIFIED, AS SHOWN ON THE PLANS OR AS DIRECTED BY THE CITY OF CITRUS HEIGHTS.

MAIN DIAMETER	MINIMUM TRENCH WIDTH
4"	18"
6"	24"
8"	24"
10"	30"
12"	30"



**CITRUS  
HEIGHTS  
WATER  
DISTRICT**

## 4" THROUGH 12" TRENCH DETAIL - PAVEMENT

**CITRUS HEIGHTS WATER DISTRICT**

APPROVED BY: Robert A. Chubb DATE: 5/8/13  
CITRUS HEIGHTS WATER DISTRICT

**FOR CONSTRUCTION IN THE CITY OF CITRUS HEIGHTS**

DRAWN: 8 MAY 2013  
REVISED:  
SCALE: N.T.S.  
DESIGN: P.A.D.  
CAD FILE: TREN\_713CH.DWG  
PAGE: **TREN\_713CH**